




A



B



C



D



E

3M

A. 3M™ Petroleum High-Capacity Sorbent Pad

Absorbs petroleum-based liquids while repelling water. Increased fluid-holding capacity means less sorbent used, minimizing sorbent waste for disposal. Low-profile design for use in tight places. Ideal for cleaning up small spills and wiping down contaminated areas. Each case absorbs 37½ gallons. 17 x 19 pad size. 100 pads per case. Shpg. wt. 20 lbs.

MCO HP-156	Case
------------	-------------

B. Safety-Walk™ General Purpose Tread Rolls

Helps prevent slips and falls in heavy-traffic work areas, ramps, walkways, loading docks, machinery, vehicles and aircraft. Low-profile design reduces trip hazard. Mineral-coated, slip-resistant material is highly durable. Pressure-sensitive adhesive covered by a removable protective liner. For use on smooth, flat surfaces. 60-ft. rolls. Black.

No.	Width	Rolls/Case	Case
MCO 19220	1"	4	
MCO 19221	2"	2	
MCO 19223	4"	1	

C. Safety-Walk™ Medium Resilient Tread Rolls

Helps prevent slips and falls for light to medium traffic and barefoot areas. Resilient, non-mineral, slip-resistant, textured material. Pressure-sensitive adhesive covered by a removable protective liner. For use on smooth, flat surfaces. Black and gray. 60-ft. rolls.

No.	Width	Rolls/Case	Case
Black			
MCO 19293	1"	4	
MCO 19294	2"	2	
MCO 19296	4"	1	
Gray			
MCO 19321	1"	4	
MCO 19323	2"	2	
MCO 19322	4"	1	

D. Caution Stripe Tape

Striped vinyl, adhesive-backed tape for marking traffic areas and physical hazards. Resists most common solvents except ketones, esters and chlorinated hydrocarbons. 2" wide x 108 ft. long.

MCO 5702-2	Roll
------------	-------------



E. ProLine™ Tri-Class Dry Chemical Fire Extinguishers

Highly effective protection against all three common classes of fires: A, B and C. Chip-resistant epoxy finish. Strong, forged aluminum valve. Reliable gauge for fast and easy pressure checks. Rechargeable and easy to service. Fits in all standard cabinets. Mounting bracket included. Manufacturer's six-year warranty.

No.	CW/UW/UL*	Each
With Nonmagnetic Aluminum Cylinder		
◆KDD 466227	2.6/4.2/1A-10B:C	
◆KDD 466112	5/8.5/3A-40B:C	
With Steel Cylinder		
◆KDD 466204	10/19/4A-60B:C	

*CW=Charge weight lbs., UW=Unit weight lbs., UL=UL rating

◆ This symbol denotes items that cannot ship via UPS.